

CHEMTRONICS INC.

MSDS #3103

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

COMPANY ADDRESS:
8125 COBB CENTER DRIVE
KENNESAW, GA 30152

PRODUCT INFORMATION: 800-TECH-401
CUSTOMER SERVICE: 800-645-5244
EMERGENCY: (CHEMTREC) 800-424-9300

REVISION DATE: JULY 15, 1996
PREPARED BY: GWEN COTTRELL

PRODUCT IDENTIFICATION: POW-R-WASH CZ CONTACT CLEANER
PRODUCT CODE: ES7300, ES7308

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS#	WT. % RANGE
CIROZANE	MIXTURE	60.0-90.0
1,1,1,2-TETRAFLUOROETHANE	811-97-2	10.0-30.0
METHYLCYCLOHEXANE	108-87-2	1.0-10.0

NOTE: FOR INDUSTRIAL USE ONLY.

SECTION 3: HAZARD IDENTIFICATION

EMERGENCY OVERVIEW: CLEAR, COLORLESS LIQUID WITH FAINT ETHEREAL ODOR.
THIS PRODUCT IS NONFLAMMABLE. LIQUID MAY IRRITATE EYES AND SKIN UNDER
REPEATED OR PROLONGED EXPOSURE. BREATHING HIGH CONCENTRATIONS OF PRODUCT
VAPOR MAY PRODUCE DIZZINESS AND NAUSEA.

POTENTIAL HEALTH EFFECTS:
EYES: LIQUID, AEROSOLS AND VAPORS OF THIS PRODUCT MAY BE IRRITATING AND CAN
CAUSE PAIN, TEARING, REDDENING AND SWELLING ACCOMPANIED BY A STINGING
SENSATION.

SKIN: PROLONGED CONTACT CAN CAUSE SKIN IRRITATION.

INGESTION: MAY BE HARMFUL IF SWALLOWED. SWALLOWING THIS MATERIAL MAY
RESULTS IN NAUSEA, VOMITING AND WEAKNESS FOLLOWED BY CENTRAL NERVOUS SYSTEM
DEPRESSION.

INHALATION: CAN BE HARMFUL IF INHALED. HIGH CONCENTRATIONS OF VAPORS IN
IMMEDIATE AREA CAN CAUSE DIZZINESS, NAUSEA AND VOMITING.

PAGE 1

SECTION 4: FIRST AID MEASURES

EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER. AFTER INITIAL FLUSHING, REMOVE
ANY CONTACT LENSES AND CONTINUE FLUSHING FOR AT LEAST 15 MINUTES. HAVE EYES
EXAMINED AND TESTED BY MEDICAL PERSONNEL IF IRRITATION DEVELOPS OR PERSISTS.

SKIN: WASH SKIN WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. GET
MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSIST. WASH CLOTHING BEFORE
REUSE.

INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. IF CONSCIOUS, GIVE 2
GLASSES OF WATER. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
KEEP HEAD BELOW KNEES TO MINIMIZE CHANCE OF ASPIRATING MATERIAL INTO THE
LUNGS. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: NONE TO BOILING (TCC)

EXTINGUISHING MEDIA: USE WATER SPRAY OR FOG, CO2, DRY CHEMICAL OR WATER STREAM WHEN FIGHTING FIRES INVOLVING THIS MATERIAL.

FIRE FIGHTING INSTRUCTIONS: AS IN ANY FIRE, WEAR SELF-CONTAINED BREATHING APPARATUS (PRESSURE-DEMAND, MSHA/NIOSH APPROVED OR EQUIVALENT) AND FULL PROTECTIVE GEAR.

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPILLS: SHUT OFF LEAK IF POSSIBLE AND SAFE TO DO SO. ABSORB SPILL WITH INERT MATERIAL (E.G. DRY SAND OR EARTH), THEN PLACE IN A CHEMICAL WASTE CONTAINER FOR PROPER DISPOSAL. DO NOT FLUSH TO SEWER. AVOID RUNOFF INTO STORM SEWERS AND DITCHES WHICH LEAD TO WATERWAYS.

SECTION 7: HANDLING AND STORAGE

AVOID PROLONGED OR REPEATED CONTACT WITH EYES, SKIN, AND CLOTHING. WASH HANDS BEFORE EATING. USE WITH ADEQUATE VENTILATION. AVOID BREATHING PRODUCT VAPOR OR MIST. DO NOT REUSE THIS CONTAINER. STORE IN A COOL DRY PLACE AWAY FROM HEAT, SPARKS, AND FLAME. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT STORE IN DIRECT SUNLIGHT. KEEP OUT OF REACH OF CHILDREN.

PAGE 2

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

(VALUES ARE FROM ACGIH GUIDE TO EXPOSURE VALUES 1994)

EXPOSURE GUIDELINES:

CHEMICAL NAME	ACGIH TWA	OSHA PEL	OTHER TLV
CIROZANE	NE	NE	545 PPM @
1,1,1,2-TETRAFLUOROETHANE	NE	NE	1000 PPM (DUPONT)
METHYLCYCLOHEXANE	400 PPM	400 PPM	400 PPM

NE = NONE ESTABLISHED

@ = CHEMTRONIC'S RECOMMENDED THRESHOLD LIMIT VALUE/VALUE BASED ON COMPUTATION

NFPA AND HMIS CODES	NFPA	HMIS
HEALTH	1	1
FLAMMABILITY	0	0
REACTIVITY	1	1
PERSONAL PROTECTION	-	B

WORK/HYGIENIC PRACTICES: GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT TO CONTROL AIRBORNE LEVELS. THIS MATERIAL DOES NOT HAVE ESTABLISHED EXPOSURE LIMITS. WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: CLEAR, COLORLESS LIQUID

ODOR: ETHEREAL ODOR

PH: NA

VAPOR PRESSURE (AIR=1): 170 PSI @ 70 F
BOILING POINT: 90 F (INITIAL)
SOLUBILITY IN WATER: NEGLIGIBLE
SPECIFIC GRAVITY (WATER=1): 1.50
EVAPORATION RATE (BUTYL ACETATE=1): GT 1
VISCOSITY: NA
PERCENT VOLATILE: 100%

SECTION 10: STABILITY AND REACTIVITY

STABILITY: THIS PRODUCT IS STABLE.
CONDITIONS TO AVOID: STEAM, OXIDIZERS, ELEVATED TEMPERATURES. DO NOT SPRAY
NEAR OPEN FLAMES, RED HOT SURFACES OR OTHER SOURCES OF IGNITION.

INCOMPATIBILITY: DO NOT MIX WITH CHEMICALLY ACTIVE METALS SUCH AS POTASSIUM,
MAGNESIUM, ZINC AND POWDERED ALUMINUM, STRONG BASE, CAUSTIC SODA, CAUSTIC
POTASH OR OXIDIZING.

PRODUCTS OF DECOMPOSITION: THERMAL DECOMPOSITION MAY RELEASE CARBON MONOXIDE,
CARBON DIOXIDE, HYDROGEN CHLORIDE AND HYDROGEN FLUORIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID: FINELY DIVIDED ACTIVE METALS, ALKALI AND ALKALINE EARTH
METALS.

PAGE 3

SECTION 11: TOXICOLOGICAL INFORMATION (NIOSH RTECS THROUGH OCTOBER 1995)

INHALATION:

CIROZANE @ LD50 RATS GT 3000 PPM
TETRAFLUOROETHANE RATS ALC 567,000 PPM/4HRS
METHYLCYCLOHEXANE LC50/MOUSE 41,500 MG/M3/2HRS

SKIN:

CIROZANE @ 500 MG/RATS MLD

INGESTION:

CIROZANE @ LD50/RATS GT 5 G/KG
METHYLCYCLOHEXANE LD50 MOUSE 2,250 MG/KG

EYE:

CIROZANE @ 150 MG/RATS/24H MLD
METHYLCYCLOHEXANE LD50 MOUSE 2,250 MG/KG

CANCER INFORMATION: NO INGREDIENTS LISTED AS HUMAN CARCINOGENS BY NTP OR IARC
@ INFORMATION PROVIDED BY MANUFACTURER.

SECTION 12: ECOLOGICAL INFORMATION

AVOID RUNOFF INTO STORM SEWERS AND DITCHES WHICH LEAD TO WATERWAYS. WATER
RUNOFF CAN CAUSE ENVIRONMENTAL DAMAGE.

REPORTING: US REGULATIONS REQUIRE REPORTING SPILLS OF THIS MATERIAL THAT
COULD REACH ANY SURFACE WATERS.

THE TOLL FREE NUMBER FOR THE US COAST GUARD NATIONAL RESPONSE CENTER IS:
1-800-424-8802.

SECTION 13: DISPOSAL CONSIDERATIONS

DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.
WATER RUNOFF CAN CAUSE ENVIRONMENTAL DAMAGE.

SECTION 14: TRANSPORTATION INFORMATION

PROPER SHIPPING NAME	UN NUMBER	CLASS	SUB. RISK	PKG. GROUP	HAZARD LABEL	PKG. INSTR.	MAX. QUANTITY
AIR: AEROSOLS NON-FLAMMABLE N.O.S.	UN 1950	2.2	NA	NA	NON-	203	75 K.G. ;

FLAMMABLE Y203 150 K.G.
GAS 30 KG

GROUND: CONSUMER COMMODITY ORM-D
NA ORM-D NA NA ORM-D PKG. 173.306
AUTH. 173.150
173.153

PAGE 4

SECTION 15: REGULATORY INFORMATION

SECTION 313 SUPPLIER NOTIFICATION:
THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICALS SUBJECT TO THE REPORTING
REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY
RIGHT-TO-KNOW ACT OF 1986 (40 CFR 372).

THERE ARE NO SECTION 313 LISTED CHEMICALS IN THIS PRODUCT.

THIS INFORMATION SHOULD BE INCLUDED ON ALL MSDSS COPIED AND DISTRIBUTED FOR
THIS MATERIAL.

TOXIC SUBSTANCES CONTROL ACT (TSCA): ALL INGREDIENTS OF THIS PRODUCT ARE
LISTED ON THE TSCA INVENTORY.

SECTION 16: OTHER INFORMATION

DO NOT PUNCTURE OR INCINERATE CONTAINERS. NORMAL VENTILATION FOR STANDARD
MANUFACTURING PRACTICES IS USUALLY ADEQUATE. LOCAL EXHAUST SHOULD BE USED
WHEN LARGE AMOUNTS ARE RELEASED.

REFERENCES: 29 CFR 1910.1200 40 CFR 300-700 ANSI Z400.1-1993
NIOSH RTECS PROVIDED BY CHEM-BANK BY SILVERPLATTER
GUIDE TO OCCUPATIONAL EXPOSURE VALUES 1994

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE.
HOWEVER, ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED WITH
CAUTION. IN PARTICULAR, IMPROPER USE OF OUR PRODUCTS AND THEIR INAPPROPRIATE
COMBINATION WITH OTHER PRODUCTS AND SUBSTANCES MAY PRODUCE HARMFUL RESULTS
WHICH CANNOT BE ANTICIPATED. FINAL DETERMINATION OF THE SUITABILITY OF ANY
MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALTHOUGH CERTAIN HAZARDS
ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS
THAT MAY EXIST.

PAGE 5 (LAST PAGE)