

Material Safety Data Sheet

Section 1. Product and Company Identification

| | | | |
|---------------------|---|-----------------------|----------|
| Product Name | Gill Modified OG-6 | Product Code | 65069 |
| Manufacturer | EMD Chemicals Inc. P.O. Box 70 480 Democrat Road Gibbstown, NJ 08027 Prior to January 1, 2003 EMD Chemicals Inc. was EM Industries, Inc. or EM Science, Division of EM Industries, Inc. | Effective Date | 3/4/2003 |
| | | Print Date | 5/3/2004 |

For More Information Call

856-423-6300 Technical Service
Monday-Friday: 8:00 AM - 5:00 PM

In Case of Emergency Call

800-424-9300 CHEMTREC (USA)
613-996-6666 CANUTEC (Canada)
24 Hours/Day: 7 Days/Week

Synonym None.

Material Uses Laboratory Reagent

Chemical Family Dye Solution

Section 2. Composition and Information on Ingredients

| Component | CAS # | % by Weight |
|----------------------|------------|-------------|
| ETHANOL | 64-17-5 | >90 |
| METHANOL | 67-56-1 | <5 |
| ACID ORANGE 10 | 1936-15-8 | <1 |
| Water | 7732-18-5 | <5 |
| PHOSPHOTUNGSTIC ACID | 12501-23-4 | <1 |

Section 3. Hazards Identification

Physical State and Appearance Liquid.

Emergency Overview DANGER !POISON !
FLAMMABLE LIQUID AND VAPOR.
VAPOR MAY CAUSE FLASH FIRE.
MAY BE FATAL IF SWALLOWED.
MAY CAUSE BLINDNESS IF SWALLOWED.
CANNOT BE MADE NON-POISONOUS
HARMFUL IF INHALED OR ABSORBED THROUGH SKIN.
CAUSES EYE AND SKIN IRRITATION.
POSSIBLE BIRTH DEFECT HAZARD.
CONTAINS MATERIAL WHICH MAY CAUSE BIRTH DEFECTS BASED ON ANIMAL DATA.

Routes of Entry Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.

Potential Acute Health Effects

Eyes Hazardous in case of eye contact (irritant). Inflammation of the eye is characterized by redness, watering, and itching.

Skin Hazardous in case of skin contact (permeator, irritant). Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

Continued on Next Page

Inhalation Hazardous in case of inhalation.

Ingestion Extremely hazardous in case of ingestion. May be fatal if swallowed.

Potential Chronic Health Effects

Carcinogenic Effects This material is not known to cause cancer in animals or humans.

Additional information See Toxicological Information (section 11)

Medical Conditions Aggravated by Overexposure:

Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

Section 4. First Aid Measures

Eye Contact

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention immediately.

Skin Contact

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flammability of the Product

Product will burn.

Auto-ignition Temperature

The lowest known value is 362.78°C (685°F) (ETHANOL).

Flash Points

The lowest known value is Closed cup: 13.333°C (56°F). (ETHANOL)

Flammable Limits

LOWER: 3.3% UPPER: 19%

Products of Combustion

These products are carbon oxides (CO, CO₂).

Fire Hazards in Presence of Various Substances

Flammable in presence of open flames, sparks and static discharge, of shocks, of heat, of oxidizing materials.

Explosion Hazards in Presence of Various Substances

Risks of explosion of the product in presence of static discharge:

Flammable in presence of open flames, sparks and static discharge.

Explosive in presence of open flames, sparks and static discharge.

Risks of explosion of the product in presence of mechanical impact:

Flammable in presence of shocks.

Explosive in presence of shocks.

Fire Fighting Media and Instructions

SMALL FIRE: Use DRY chemical powder.

LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.

Protective Clothing (Fire)

Be sure to use an approved/certified respirator or equivalent.

Special Remarks on Fire Hazards

Dangerous fire and explosion risk. Container explosion may occur under fire conditions or when heated. Vapor may travel considerable distance to source of ignition and flash back. (METHANOL)

Special Remarks on Explosion Hazards

Dangerous fire and explosion risk. Vapor may travel considerable distance to source of ignition and flash back.

Continued on Next Page

Section 6. Accidental Release Measures

| | |
|------------------------------|--|
| Small Spill and Leak | Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container. |
| Large Spill and Leak | Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain. Do not get water inside container. Do not touch spilled material. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities. |
| Spill Kit Information | The following EMD Chemicals Inc. SpillSolv (TM) absorbent is recommended for this product: SX1330 Solvent Treatment Kit |

Section 7. Handling and Storage

| | |
|-----------------|---|
| Handling | Keep away from heat, sparks and flame. Use only with adequate ventilation. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. |
| Storage | Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). |

Section 8. Exposure Controls/Personal Protection

| | |
|-----------------------------|---|
| Engineering Controls | Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location. |
| Personal Protection | |
| Eyes | Splash goggles. |
| Body | Lab coat. |
| Respiratory | Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. |
| Hands | Gloves. |
| Feet | Not applicable. |

Protective Clothing (Pictograms)**Personal Protection in Case of a Large Spill**

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Product Name

ETHANOL

Exposure Limits**AUVA (Austria, 1995).**Spitzenbegrenzung: 3800 mg/m³ 3 times per shift, Period: 60 minute(s).

Spitzenbegrenzung: 2000 ML/M3 3 times per shift, Period: 60 minute(s).

TWA: 1900 mg/m³

TWA: 1000 ML/M3

NOHSC (Australia, 1995).TWA: 1880 mg/m³

TWA: 1000 ppm

Lijst Grenswaarden (Belgium, 1998).VL: 1907 mg/m³

VL: 1000 ppm

SUVA (Switzerland, 1997).MAK: 1900 mg/m³

MAK: 1000 ML/M3

Ministry of Health (CL, 1992).TWA: 1500 mg/m³

TWA: 800 ppm

MAK-Werte Liste (Germany, 1998).Spitzenbegrenzung: 1920 mg/m³ 4 times per shift, Period: 30 minute(s).

Spitzenbegrenzung: 1000 ML/M3 4 times per shift, Period: 30 minute(s).

MAK: 960 mg/m³

MAK: 500 ML/M3

TRGS900 (Germany, 1999).Spitzenbegrenzung: 7600 mg/m³

Spitzenbegrenzung: 4000 ML/M3

MAK: 1900 mg/m³

MAK: 1000 ML/M3

Arbejdstilsynet (Denmark, 1996).GV: 1900 mg/m³

GV: 1000 ppm

Tyterveyslaitos (Finland, 1998).STEL: 2500 mg/m³

STEL: 1300 ppm

TWA: 1900 mg/m³

TWA: 1000 ppm

INRS (France, 1999).VLE: 9500 mg/m³

VLE: 5000 ppm

VME: 1900 mg/m³

VME: 1000 ppm

EH40-OES (United Kingdom (UK), 2000).TWA: 1920 mg/m³

TWA: 1000 ppm

NAOSH (Ireland, 1999).OEL: 1900 mg/m³

OEL: 1000 ppm

Ministry of Labour (KR, 1997).TWA: 1900 mg/m³

TWA: 1000 ppm

Secretary of Work and Social security (MX, 1994).CPT: 1900 mg/m³ Period: 8 hour(s).

CPT: 1000 ppm Period: 8 hour(s).

Nationale MAC-lijst (Netherlands, 2000).TGG 8 uur: 1000 mg/m³

TGG 8 uur: 500 ppm

NZ OSH (NZ, 1994).TWA: 1880 mg/m³

TWA: 1000 ppm

AFS (Sweden, 1996).TGV: 1900 mg/m³

TGV: 1000 ppm

NGV: 1000 mg/m³

NGV: 500 ppm

ACGIH TLV (United States, 2000).TWA: 1880 mg/m³

TWA: 1000 ppm

NIOSH REL (United States, 2000).TWA: 1900 mg/m³ Period: 10 hour(s).

TWA: 1000 ppm Period: 10 hour(s).

OSHA Final Rule (United States, 1989).TWA: 1900 mg/m³

TWA: 1000 ppm

ACGIH (United States, 1994). SkinTWA: 262 mg/m³

METHANOL

STEL: 328 mg/m³
OSHA (United States, 1989). Skin
 TWA: 260 mg/m³
 STEL: 325 mg/m³
ACGIH (United States, 1994). Skin
 STEL: 328 mg/m³
 STEL: 250 ppm
 TWA: 262 mg/m³
 TWA: 200 ppm
NIOSH REL (United States, 1994). Skin
 STEL: 325 mg/m³
 STEL: 250 ppm
 TWA: 260 mg/m³ Period: 10 hour(s).
 TWA: 200 ppm Period: 10 hour(s).
OSHA Final Rule (United States, 1989). Skin
 STEL: 325 mg/m³
 STEL: 250 ppm
 TWA: 260 mg/m³
 TWA: 200 ppm
 ACID ORANGE 10 Not available.
 Water Not available.
 PHOSPHOTUNGSTIC ACID Not available.

Section 9. Physical and Chemical Properties

| | |
|--------------------------------------|---|
| Odor | Alcohol like. |
| Color | Orange. |
| Physical State and Appearance | Liquid. |
| Molecular Weight | Not applicable. |
| Molecular Formula | Not applicable. |
| pH | Not available. |
| Boiling/Condensation Point | The lowest known value is 64.55°C (148.2°F) (METHANOL). Weighted average: 78.72°C (173.7°F) |
| Melting/Freezing Point | May start to solidify at -0.1°C (31.8°F) based on data for: Water. Weighted average: -7.95°C (17.7°F) |
| Specific Gravity | Weighted average: 0.79 (Water = 1) |
| Vapor Pressure | The highest known value is 12.9 kPa (97 mmHg) (@ 20°C) (METHANOL). Weighted average: 6.26 kPa (46.95 mmHg) (@ 20°C) |
| Vapor Density | The highest known value is 1.59 (Air = 1) (ETHANOL). Weighted average: 1.57 (Air = 1) |
| Volatility | 99.9% (v/v). (METHANOL.) |
| Odor Threshold | The lowest known value is 5 ppm (ETHANOL) Weighted average: 9.91 ppm |
| Evaporation Rate | The highest known value is 5.91 (METHANOL) Weighted average: 1.84 compared to (n-BUTYL ACETATE=1) |
| VOC | 95 (%) |
| LogK_{ow} | Not available. |
| Solubility | Soluble in water. |

Continued on Next Page

Section 10. Stability and Reactivity

| | |
|--|---|
| Stability and Reactivity | The product is stable. |
| Conditions of Instability | FLAMMABLE LIQUID AND VAPOR. (ETHANOL) |
| Incompatibility with Various Substances | Reactive with oxidizing agents, acids. Slightly reactive to reactive with metals. |
| Rem/Incompatibility | Avoid all possible sources of ignition (spark or flame). Reacts with heavy metals and metallic salts. |
| Hazardous Decomposition Products | COx , Formaldehyde. , Cl |
| Hazardous Polymerization | Will not occur. |

Section 11. Toxicological Information

| | | |
|--|--|--|
| RTECS Number: | Ethanol Methanol Orange G Water Phosphotungstic Acid | KQ6300000 PC1400000 QJ6500000 ZC0110000 Not available. |
| Toxicity | Acute oral toxicity (LD ₅₀): 3450 mg/kg [Mouse]. (ETHANOL). Acute dermal toxicity (LD ₅₀): 15800 mg/kg [Rabbit]. (METHANOL). Acute toxicity of the vapor (LC ₅₀): 20000 ppm 10 hour(s) [Rat]. (ETHANOL). | |
| Chronic Effects on Humans | DEVELOPMENTAL TOXICITY: Classified Reproductive system/toxin/female, Reproductive system/toxin/male [SUSPECTED] [ETHANOL]. Contains material which may cause damage to the following organs: blood, the reproductive system, liver. | |
| Acute Effects on Humans | Hazardous in case of eye contact (irritant). Inflammation of the eye is characterized by redness, watering, and itching. Hazardous in case of skin contact (permeator, irritant). Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering. Hazardous in case of inhalation. Extremely hazardous in case of ingestion. May be fatal if swallowed. | |
| Synergetic Products (Toxicologically) | Not available. | |
| Irritancy | <u>Draize Test:</u> Not available. | |
| Sensitization | Not available. | |
| Carcinogenic Effects | This material is not known to cause cancer in animals or humans. | |
| Toxicity to Reproductive System | Classified Reproductive system/toxin/female, Reproductive system/toxin/male [SUSPECTED] [ETHANOL]. | |
| Teratogenic Effects | Not available. | |
| Mutagenic Effects | Not available. | |

Section 12. Ecological Information

| | |
|---|---|
| Ecotoxicity | Not available. |
| BOD5 and COD | Not available. |
| Toxicity of the Products of Biodegradation | The products of degradation are less toxic than the product itself. |

Section 13. Disposal Considerations

| | |
|-------------------------|--|
| EPA Waste Number | D001 |
| Treatment | Incineration, fuels blending or recycle. Contact your local permitted waste disposal site (TSD) for permissible treatment sites. ALWAYS CONTACT PERMITTED WASTE DISPOSER (TSD) TO ASSURE COMPLIANCE WITH ALL CURRENT LOCAL, STATE AND FEDERAL REGULATIONS. |

Section 14. Transport Information

| | |
|---------------------------------|----------------|
| DOT Classification | Not available. |
| TDG Classification | Not available. |
| IMO/IMDG Classification | Not available. |
| ICAO/IATA Classification | Not available. |

Section 15. Regulatory Information

| | |
|---------------------------------|--|
| U.S. Federal Regulations | TSCA 8(b) inventory: ETHANOL; METHANOL; ACID ORANGE 10; Water; PHOSPHOTUNGSTIC ACID SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: ETHANOL; METHANOL; ACID ORANGE 10 SARA 311/312 MSDS distribution - chemical inventory - hazard identification: ETHANOL: Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; METHANOL: Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; ACID ORANGE 10: Delayed (Chronic) Health Hazard SARA 313 toxic chemical notification and release reporting: METHANOL 4.95% Clean Water Act (CWA) 307: No products were found. Clean Water Act (CWA) 311: No products were found. Clean air act (CAA) 112 accidental release prevention: No products were found. Clean air act (CAA) 112 regulated flammable substances: No products were found. Clean air act (CAA) 112 regulated toxic substances: No products were found. |
|---------------------------------|--|

| | |
|-----------------------|---|
| WHMIS (Canada) | CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). Class D-1B: Material causing immediate and serious toxic effects (TOXIC). Class D-2B: Material causing other toxic effects (TOXIC). |
|-----------------------|---|

CEPA DSL: ETHANOL; METHANOL; ACID ORANGE 10; Water

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations and the MSDS contains all required information.

International Regulations

| | | |
|---------------|----------------------|----------------|
| EINECS | ETHANOL | 200-578-6 |
| | METHANOL | 200-659-6 |
| | ACID ORANGE 10 | 217-705-6 |
| | Water | 231-791-2 |
| | PHOSPHOTUNGSTIC ACID | Not available. |

| | |
|-------------------|---|
| DSCL (EEC) | R20/21/22- Harmful by inhalation, in contact with skin and if swallowed. R40/20/21/22- Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed. |
|-------------------|---|

International Lists Australia (NICNAS): ETHANOL; METHANOL; ACID ORANGE 10; Water; PHOSPHOTUNGSTIC ACID

Germany water class: ETHANOL

Japan (MITI): ETHANOL; METHANOL; ACID ORANGE 10; Water; PHOSPHOTUNGSTIC ACID

Korea (TCCL): ETHANOL; METHANOL; ACID ORANGE 10; Water

Philippines (RA6969): ETHANOL; METHANOL; ACID ORANGE 10; Water

China: No products were found.

State Regulations

Pennsylvania RTK: ETHANOL: (generic environmental hazard); METHANOL: (environmental hazard, generic environmental hazard)

Massachusetts RTK: ETHANOL; METHANOL

New Jersey: Gill Modified OG-6

California prop. 65: No products were found.

Section 16. Other Information

**National Fire
Protection
Association
(U.S.A.)**



**Changed Since Last
Revision**

+

Notice to Reader

The statements contained herein are based upon technical data that EMD Chemicals Inc. believes to be reliable, are offered for information purposes only and as a guide to the appropriate precautionary and emergency handling of the material by a properly trained person having the necessary technical skills. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use, storage and disposal of these materials and the safety and health of employees and customers and the protection of the environment. EMD CHEMICALS INC. MAKES NO REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, WITH RESPECT TO THE INFORMATION HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS.