



Material Safety Data Sheet

Section 1. Product and Company Identification

Product Name	May & Grunwald's Stain	Product Code	660
Manufacturer	EMD Chemicals Inc. P.O. Box 70 480 Democrat Road Gibbstown, NJ 08027 Prior to January 1, 2003 EMD Chemicals Inc. was EM Industries, Inc. or EM Science, Division of EM Industries, Inc.	Effective Date	4/19/2005
		Print Date	5/17/2005

For More Information Call

856-423-6300 Technical Service
Monday-Friday: 8:00 AM - 5:00 PM

In Case of Emergency Call

800-424-9300 CHEMTREC (USA)
613-996-6666 CANUTEC (Canada)
24 Hours/Day: 7 Days/Week

Synonym None.

Material Uses Laboratory Reagent

Chemical Family Dye Solution

Section 2. Composition and Information on Ingredients

Component	CAS #	% by Weight
Eosin Y	17372-87-1	0.05
Methylene Blue	61-73-4	0.01
Water	7732-18-5	>0.94
Jenner Stain is known under CAS#62851-42-7 (Mixture of Eosin Yellow, Methylene Blue and Water)		
Methanol	67-56-1	>99

+ Section 3. Hazards Identification

Physical State and Appearance Liquid.

Emergency Overview DANGER !
POISON !
FLAMMABLE LIQUID AND VAPOR.
VAPOR MAY CAUSE FLASH FIRE.
HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED.
CANNOT BE MADE NON-POISONOUS
MAY CAUSE BLINDNESS IF SWALLOWED.
MAY BE FATAL IF INHALED.
CAUSES EYE AND SKIN IRRITATION.
CONTAINS MATERIAL WHICH CAUSES DAMAGE TO THE FOLLOWING ORGANS:
GASTROINTESTINAL TRACT, RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, EYE, LENS OR CORNEA.

Routes of Entry Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.

Potential Acute Health Effects

Eyes Hazardous in case of eye contact (irritant). Inflammation of the eye is characterized by redness, watering, and itching.

Continued on Next Page

Skin Hazardous in case of skin contact (permeator, irritant). Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

Inhalation Extremely hazardous in case of inhalation. May be fatal if inhaled.

Ingestion Hazardous in case of ingestion. Do not take internally.

Potential Chronic Health Effects

Carcinogenic Effects This material is not known to cause cancer in animals or humans.

Additional information See Toxicological Information (section 11)

Medical Conditions Aggravated by Overexposure:

Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

Section 4. First Aid Measures

Eye Contact Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention immediately.

Skin Contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion If swallowed, do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flammability of the Product Product will burn

Auto-ignition Temperature The lowest known value is 464.05°C (867.3°F) (METHANOL).

Flash Points The lowest known value is Open cup: 15.9°C (60.6°F). (METHANOL)

Flammable Limits The greatest known range is LOWER: 6% UPPER: 36.5% (METHANOL)

Products of Combustion These products are carbon oxides (CO, CO₂).

Fire Hazards in Presence of Various Substances Highly flammable in presence of open flames, sparks and static discharge, of shocks, of heat, of oxidizing materials.

Explosion Hazards in Presence of Various Substances
Risks of explosion of the product in presence of static discharge:
Highly flammable in presence of open flames, sparks and static discharge.
Highly explosive in presence of open flames, sparks and static discharge.

Risks of explosion of the product in presence of mechanical impact:
Highly flammable in presence of shocks.
Highly explosive in presence of shocks.

Fire Fighting Media and Instructions
SMALL FIRE: Use DRY chemical powder.
LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.

Protective Clothing (Fire) Be sure to use an approved/certified respirator or equivalent.

Special Remarks on Fire Hazards Fire/Explosion Hazards.
Vapor may travel considerable distance to source of ignition and flash back.

Special Remarks on Explosion Hazards Flammable gas and vapor.

Section 6. Accidental Release Measures

Small Spill and Leak Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.

Large Spill and Leak Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

Spill Kit Information The following EMD Chemicals Inc. SpillSolv (TM) absorbent is recommended for this product: SX1330 Solvent Treatment Kit

Section 7. Handling and Storage

Handling Keep away from heat, sparks and flame. Keep container closed. Use only with adequate ventilation. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment.

Storage Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

Section 8. Exposure Controls/Personal Protection

Engineering Controls Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal Protection

Eyes Splash goggles.


Body Lab coat.

Respiratory Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate.

Hands Gloves.

Feet Not applicable.

Protective Clothing (Pictograms)



Personal Protection in Case of a Large Spill

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Product Name

Eosin Y
Methylene Blue
Water
Jenner Stain is known under CAS#62851-42-7
(Mixture of Eosin Yellow, Methylene Blue and Water)
Methanol

Exposure Limits

Not available.
Not available.
Not available.

ACGIH (United States, 1994). Skin

TWA: 262 mg/m³
STEL: 328 mg/m³

OSHA (United States, 1989). Skin

TWA: 260 mg/m³

STEL: 325 mg/m³**ACGIH (United States, 1994). Skin**STEL: 328 mg/m³ 15 minute(s).

STEL: 250 ppm 15 minute(s).

TWA: 262 mg/m³ 8 hour(s).

TWA: 200 ppm 8 hour(s).

NIOSH REL (United States, 1994). SkinSTEL: 325 mg/m³ 15 minute(s).

STEL: 250 ppm 15 minute(s).

TWA: 260 mg/m³ 10 hour(s).

TWA: 200 ppm 10 hour(s).

OSHA Final Rule (United States, 1989). SkinSTEL: 325 mg/m³ 15 minute(s).

STEL: 250 ppm 15 minute(s).

TWA: 260 mg/m³ 8 hour(s).

TWA: 200 ppm 8 hour(s).

Section 9. Physical and Chemical Properties

Odor	Alcohol like.
Color	Purple to Deep Blue
Physical State and Appearance	Liquid.
Molecular Weight	Not applicable.
Molecular Formula	Not applicable.
pH	Not available.
Boiling/Condensation Point	64.5°C (148.1°F)
Melting/Freezing Point	-98°C (-144.4°F)
Specific Gravity	0.791 (Water = 1)
Vapor Pressure	12.9 kPa (97 mmHg) (@ 20°C)
Vapor Density	1.1 (Air = 1)
Volatility	99.9% (v/v). (METHANOL.)
Odor Threshold	The lowest known value is 100 ppm (METHANOL)
Evaporation Rate	5.91 (Methanol) compared to (n-Butyl Acetate =1)
VOC	99 (%)
LogK_{ow}	Not available.
Solubility	Soluble in water.

Section 10. Stability and Reactivity

Stability and Reactivity	The product is stable.
Conditions of Instability	Not available.
Incompatibility with Various Substances	Reactive with oxidizing agents, metals, acids.
Rem/Incompatibility	Avoid Heat Explodes when heated. Incompatible with nitric acid, trioxide, hydrogen peroxide, silver nitrate, perchlorates.

Continued on Next Page

Hazardous Decomposition Products COx

Hazardous Polymerization Will not occur.

Section 11. Toxicological Information

RTECS Number:

Eosin Y (Yellowish)	LM5850000
Methylene Blue	SO5600000
Water	ZC0110000
Methanol	PC1400000

Toxicity Acute oral toxicity (LD₅₀): 5628 mg/kg [Rat]. (METHANOL).
Acute dermal toxicity (LD₅₀): 15800 mg/kg [Rabbit]. (METHANOL).
Acute toxicity of the vapor (LC₅₀): 64000 ppm 4 hour(s) [Rat]. (METHANOL).

Chronic Effects on Humans Not available.

Acute Effects on Humans Hazardous in case of eye contact (irritant). Inflammation of the eye is characterized by redness, watering, and itching. Hazardous in case of skin contact (permeator, irritant). Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering. Extremely hazardous in case of inhalation. May be fatal if inhaled. Hazardous in case of ingestion.

Synergetic Products (Toxicologically) Not available.

Irritancy Draize Test: Not available.

Sensitization Not available.

Carcinogenic Effects This material is not known to cause cancer in animals or humans.

Toxicity to Reproductive System Not available.

Teratogenic Effects Not available.

Mutagenic Effects Not available.

Section 12. Ecological Information

Ecotoxicity Not available.

BOD5 and COD Not available.

Toxicity of the Products of Biodegradation The products of degradation are less toxic than the product itself.

Section 13. Disposal Considerations

EPA Waste Number U154 D001

Treatment Incineration, fuels blending or recycle. Contact your local permitted waste disposal site (TSD) for permissible treatment sites. ALWAYS CONTACT PERMITTED WASTE DISPOSER (TSD) TO ASSURE COMPLIANCE WITH ALL CURRENT LOCAL, STATE AND FEDERAL REGULATIONS.

Section 14. Transport Information

DOT Classification Proper Shipping Name: METHANOL SOLUTION
 Hazard Class: 3
 UN number: UN1230
 Packing Group: II
 RQ: Not applicable.



TDG Classification Not available.

IMO/IMDG Classification Not available.

ICAO/IATA Classification Not available.

Section 15. Regulatory Information

U.S. Federal Regulations TSCA 8(b) inventory: Eosin Y; Methylene Blue; Water; Methanol
 SARA 302/304/311/312 extremely hazardous substances: No products were found.
 SARA 302/304 emergency planning and notification: No products were found.
 SARA 302/304/311/312 hazardous chemicals: Methylene Blue; Methanol
 SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Methylene Blue: Delayed (Chronic) Health Hazard; Methanol: Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard
 SARA 313 toxic chemical notification and release reporting: METHANOL 99.99%
 Clean Water Act (CWA) 307: No products were found.
 Clean Water Act (CWA) 311: No products were found.
 Clean air act (CAA) 112 accidental release prevention: No products were found.
 Clean air act (CAA) 112 regulated flammable substances: No products were found.
 Clean air act (CAA) 112 regulated toxic substances: No products were found.

WHMIS (Canada) CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).
 Class D-1A: Material causing immediate and serious toxic effects (VERY TOXIC).
 Class D-2B: Material causing other toxic effects (TOXIC).

CEPA DSL: Eosin Y; Methylene Blue; Water; Methanol

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations and the MSDS contains all required information.

International Regulations

EINECS

Eosin Y	241-409-6
Methylene Blue	200-515-2
Water	231-791-2
Methanol	200-659-6

DSCL (EEC) R11- Highly flammable.
 R37/38- Irritating to respiratory system and skin.
 R41- Risk of serious damage to eyes.

International Lists Australia (NICNAS): Eosin Y; Methylene Blue; Water; Methanol

Japan (MITI): Eosin Y; Methylene Blue; Water; Methanol

Korea (TCCL): Eosin Y; Methylene Blue; Water; Methanol

Philippines (RA6969): Eosin Y; Methylene Blue; Water; Methanol

China: No products were found.

State Regulations Pennsylvania RTK: Methanol: (environmental hazard, generic environmental hazard)
 Massachusetts RTK: Methanol
 New Jersey: May & Grunwald's Stain
 California prop. 65: No products were found.

Continued on Next Page

Section 16. Other Information

National Fire
Protection
Association
(U.S.A.)



Changed Since Last
Revision

+

Notice to Reader

The statements contained herein are based upon technical data that EMD Chemicals Inc. believes to be reliable, are offered for information purposes only and as a guide to the appropriate precautionary and emergency handling of the material by a properly trained person having the necessary technical skills. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use, storage and disposal of these materials and the safety and health of employees and customers and the protection of the environment. EMD CHEMICALS INC. MAKES NO REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, WITH RESPECT TO THE INFORMATION HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS.